



# DISPOSABLE CORDED EARPLUGS

## DP1001 Series

ANSI/ASA S3.19-1974 | CE/UKCA EN 352:2020

NRR 31dB | SNR 37dB

Disposable corded earplugs expand to fit ear canal // Closed cell foam earplugs are resistant to dirt build up

● DP1001      Hi-Vis Orange

### Earplug Breakdown

|                                         |
|-----------------------------------------|
| Reusable: No                            |
| Metal Detectable: No                    |
| Size: One size fits most                |
| Plug Material: Polyurethane Foam        |
| Plug Dimensions: 2.6 x 1.2 cm           |
| Plug Shape: Tapered                     |
| Cord Color: Hi-Vis Lime                 |
| Cord Material: Polyvinyl Chloride (PVC) |
| Cord Length: 112 cm                     |

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov



### Packaging

DP1001 - Sold Individually | 100 per box | 10 boxes per case

### Product Guidelines

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).

2. The NRR is 26 decibels (dB).

3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.

**i** All hearing protection meets ANSI/ASA S3.19-1974 standards. Some options meet European (CE/UKCA EN-352:2002) standards. For more information visit our website or contact your sales representative.